



SECURELY
for living

HD Camera - Indoor



NZLES800HD-ID

Indoor network HD camera

Product

The HD Indoor Camera (HDCI) is an indoor network 1MP HD cube camera which is fully integrated with SECURELY for living. Using its Wi-Fi capability, the HDCI communicates with SECURELY for living through the LAN on the premises. Features include:

- Plug-and-Play Internet (IP) connectivity using Wi-Fi/LAN
- Easy installation
- High quality picture resolution with multiple compression formats
- Live view with audio capability viewable from the SECURELY for living mobile app.
- Continuous cloud recording with a range of storage levels.
- Accessories include a bracket to install the camera on a flat surface or wall (with screws)

SECURELY for living

The SECURELY for living suite allows living life fully through smart connected homes

- Home security, safety and home automation at the core
- Notifications of security events and remote management of the home in real time
- Modular and expandable - manage connected home devices with Z-Wave® expansion
- Smart Rule engine for automation – decide which device, condition, or event will trigger which actions and at what time
- Live HD video – anytime, on any screen
- Save energy and money by ensuring that lights and air conditioning are turned off when not at home

For more information go to <http://www.securely.nz> or call 0800 904 904



SECURELY
for living

Specifications

COMMUNICATIONS

- **Ethernet:** 10BASE-T / 100BASE-TX, RJ45 connector
- **Wireless:** IEEE802.11n / b / g

CAMERA

- **Image sensor:** Approximately 1/4 type CMOS image sensor
- **Picture encoding:** H.264/MJPEG, MPEG
- **Pixels:** 1280 (H) x 720 (V) approximately 1.0 megapixel
- **Resolution:** 720P (1280 x 720) / 640 x 360 / 320 x 180
- **Lens focal length:** 2.5 mm
- **Lens focus range:** 0.3 m
- **Angular field of view (FOV):** Horizontal 88°, Vertical 46°

POWER

- DC 12 V (Use only with AC adapter)
- **Consumption:** Max 4.7 W

DIMENSIONS

- **Size:** H: 43 mm, L: 99 mm, W: 67 mm
- **Weight:** 170 g including bracket

ENVIRONMENT

- **Storage Ambient Temperature range:** -20°C – +60°C
- **Operating Ambient Temperature range:** 0°C – +40°C
- **RF Operating Humidity:** Up to 95% non-condensing

