

Product

Unique combination of Passive Infrared (PIR) motion detection and image capture Camera:

Features include:

- Smartphone and web applications that allow viewing both comfort images and security images, triggered by motion detection
- Compressed, captured, image-data, relayed to the cloud, via the SECURELY for living Hub, using the ECOP protocol
- Camera lens field of view (FoV) of 67°
- Multi-zone spherical lens for exceptional detection coverage (90° horizontal, 105° vertical)
- Sealed optics, immune to external light and insects, that reduces false alarms
- Efficient power consumption to extend the operation period
- Support of automatic over-the-air software programming and configuration upgrade (RSU)
- Red LED walk-through test mode (30 minutes after power-up)
- Bright white LED to illuminate a dark environment
- Easy installation: Double-sided adhesive tape

SECURELY for living

The SECURELY for living suite allows living life fully through smart connected homes

- · Home security and safety at the core
- Notifications of security events and remote management of the home in real time
- Modular and expandable manage connected home devices with Z-Wave® expansion
- Smart Rule engine for automation decide which device, condition, or event will trigger which actions and at what time
- Live HD video anytime, on any screen
- Save energy and money by ensuring that lights and air conditioning are turned off when not at home

Camera Detector



Specifications

COMMUNICATION

Maximum RF Range: 500 m open air
Maximum Transmission: 25 mW (14 dBm)
Proprietary bi-directional radio protocol

Modulation and Frequency: DSSS, 2.4 GHz

Data Security: 128 bit AES encryption

SECURITY

- Tamper Alarm: when unit is tilted
- Detection Range up to 12 m

IMAGE CAPTURE

- Captures colour Motion: JPEG photos (up to 5 frames per second)
- Resolution for comfort video: 256x192
- Resolution for security video: 320x240
- Illumination (at night or in low-light conditions): auto-activated super- bright white LED
- **Diagonal shooting angle**: 67° with an option for 90°
- Camera Range up to 10 m

POWER CONSUMPTION

- Three AA-size alkaline batteries
- One year battery life

DIMENSIONS

- Size: H: 60 mm, L: 122.7 mm, W: 58 mm
- Weight: 160 g (not including batteries)

ENVIRONMENT

- Storage Ambient Temperature range: -20°C +50°C
- Operating Ambient Temperature range with batteries: $0^{\circ}C +50^{\circ}C$
- RF Operating Humidity: Up to 95% non-condensing

SPECIAL FEATURES

- 4G DragonFlyEye™ lens technology for optional pet immunity
- Temperature compensation for the PIR element

For more information go to http://www.securely.nz or call 0800 904 904





