



SECURELY
for living

Product

The stand alone, 24x7, integrated smoke alarm, featuring:

- Visual indication with tri-color LED:
 - o Red – Smoke alarm
 - o Green – Power status
 - o Yellow – Low battery or chamber degradation
- Works with, and independently of, SECURELY for living - emits an alarm even when the hub is disabled
- Test/Mute button
- Efficient power consumption to extend the operation period
- Siren emits sound of 85dBA (from 3m)
- Supports automatic over-the-air programming and configuration software upgrade (RSU)
- Accessories:
 - o Two Philips Cross Recessed Flat Countersunk Head screws type DIN7892C ST3.5x32
 - o Two Plastic Series 108 Dowels Drill Hole Diameter 5mm length 25mm

SECURELY for living

The SECURELY for living suite allows living life fully through smart connected homes

- Home security, safety and home automation at the core
- Notifications of security events and remote management of the home in real time
- Modular and expandable - manage connected home devices with Z-Wave® expansion
- Smart Rule engine for automation – decide which device, condition, or event will trigger which actions and at what time
- Live HD video – anytime, on any screen
- Save energy and money by ensuring that lights and air conditioning are turned off when not at home

For more information go to <http://www.securely.nz> or call 0800 904 904



SECURELY
for living

Smoke Alarm



NZLES800SK2 Optical Smoke Alarm

Specifications

COMMUNICATION

- **Maximum RF Range:** 500 m open air
- **Maximum Transmission:** 25 mW (14 dBm)
- Proprietary bi-directional radio protocol
- **Modulation and Frequency:** DSSS, 2.4 GHz

SECURITY

- **Tamper Alarm:** when detached from base
- **Concurrent operation modes:** Integrated with the SECURELY for living system yet also independent of SECURELY for living hub operation

POWER CONSUMPTION

- Two AA-size alkaline batteries
- Two-year battery life
- Mechanism prevents installation without battery

DIMENSIONS

- **Size:** H: 46.7 mm, Diameter: 135 mm
- **Weight:** 210 g including batteries

ENVIRONMENT

- **Storage Ambient Temperature range:** -20°C – +50°C
- **Operating Ambient Temperature range with batteries:** 0°C – +50°C
- **RF Operating Humidity:** Up to 95% non-condensing

